

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A transceiver comprising:

a transmitting and receiving electrode that induces an electric field in an electric field transmission medium, and receives the electric field induced in said electric field transmission medium;

a transceiver main body that generates said electric field based on information to be transmitted in said transmitting and receiving electrode, and converts said electric field generated in said transmitting and receiving electrode into reception information, thereby transmitting and receiving information via said electric field transmission medium;

a first structure that is interposed between said transmitting and receiving electrode and said electric field transmission medium;

a second structure that is interposed between said transceiver main body and said electric field transmission medium;

a battery that drives said transceiver main body; and

a third structure that is interposed between said transceiver main body and said battery, wherein

~~each of~~ said first, said second, and said third structures are composed of ~~at least one of metal, a semiconductor, and an insulator, and are~~ are equivalent to a parallel circuit of a resistor and a capacitor.

2. (Previously Presented) The transceiver according to claim 1, wherein the impedance of said second structure and the impedance of said third structure are larger than the impedance of said first structure.

3. (Previously Presented) The transceiver according to claim 2, wherein said first structure is an insulating film that covers said transmitting and receiving electrode against said electric field transmission medium.
4. (Previously Presented) The transceiver according to claim 2, wherein said second structure and said third structure are insulating members.
5. (Previously Presented) A transceiver comprising:
 - a transceiver main body that induces an electric field based on information to be transmitted in an electric field transmission medium from a transmitting electrode, thereby transmitting the information via said electric field transmission medium;
 - a battery that drives said transceiver main body; and
 - an insulating case that incorporates said transceiver main body, wherein said transmitting electrode is provided on the whole surface of a portion of an external wall surface of said insulating case, said electric field transmission medium closely approaching the portion, and is covered with an insulating film so as not to be in direct contact with said electric field transmission medium.
6. (Previously Presented) The transceiver according to claim 5, further comprising an insulating member between said battery and said transceiver main body.
7. (Previously Presented) The transceiver according to claim 6, wherein said insulating member is a foam member containing air.
8. (Previously Presented) The transceiver according to claim 6, wherein said insulating member is a plurality of wooden pillars.
9. (Original) The transceiver according to claim 6, wherein said insulating member is a cushion member having predetermined gas confined therein.

10. (Previously Presented) The transceiver according to claim 5, further comprising a ground electrode that defines a reference voltage which is necessary to drive said transceiver main body, and that is attached to an internal wall surface of said insulating case.

11. (Previously Presented) The transceiver according to claim 5, further comprising a ground electrode that defines a reference voltage which is necessary to drive said transceiver main body, and that is attached to an external device at the outside of said insulating case.

12. (Previously Presented) A transceiver comprising:

a transceiver main body that induces an electric field based on information to be transmitted in an electric field transmission medium from a transmitting electrode, and receives information based on the electric field induced in said electric field transmission medium with a receiving electrode, thereby transmitting and receiving the information via said electric field transmission medium;

a battery that drives said transceiver main body; and

an insulating case that incorporates said transceiver main body, wherein

said transmitting electrode is provided on the whole surface of a portion of an external wall surface of said insulating case, said electric field transmission medium closely approaching the portion, and is covered with a first insulating film so as not to be in direct contact with said electric field transmission medium, and

said receiving electrode is provided on an external wall surface of said first insulating film, and is covered with a second insulating film so as not to be in direct contact with said electric field transmission medium.

13. (Previously Presented) A transceiver comprising:

a transceiver main body that induces an electric field based on information to be transmitted in an electric field transmission medium from a transmitting electrode, and receives information based on the electric field induced in said electric field transmission

medium with a receiving electrode, thereby transmitting and receiving the information via said electric field transmission medium;

a battery that drives said transceiver main body; and

an insulating case that incorporates said transceiver main body, wherein

said receiving electrode is provided on the whole surface of a portion of an external wall surface of said insulating case, said electric field transmission medium closely approaching the portion, and is covered with a first insulating film so as not to be in direct contact with said electric field transmission medium, and

said transmitting electrode is provided on an external wall surface of said first insulating film, and is covered with a second insulating film so as not to be in direct contact with said electric field transmission medium.

14. – 32. (Canceled)